

To All Customers

Rep No. C23007

July 21, 2023

Fuji Electric FA Components
& Systems Co., Ltd.

JIS Compatible Earth Leakage Circuit Breakers
Notification regarding Production Discontinuation of DV32, DV33, DG32 Series Products


We would like to thank you for your continued patronage of Fuji products.
 We are writing to announce the production discontinuation of some of our products.
 Details are described below. Please review the following information and take appropriate actions.
 Please also inform all related sections of your company of this discontinuation.

Product name	JIS Compatible Earth Leakage Circuit Breakers
Series name	DV32, DV33, DG32 Series
Type	DV32/30-◆, DV33/30-◆ DG32/15-◆, DG32/20-◆, DG32/30-◆ ◆: Rated sensitivity current value *All models, including special specifications of the above types
Reason for discontinuation	Production discontinuation due to withdrawal from the JIS compatible earth leakage circuit breaker business.
Alternative models	There are no alternative Fuji products. Please refer to the attachment "JIS Compatible Earth Leakage Circuit Breaker DV32, DV33, DG32 Series Alternative Product Comparison."
Date of production discontinuation	December 31, 2023
Attachments	Attachment 1: "JIS Compatible Earth Leakage Circuit Breaker DV32, DV33, DG32 Series Alternative Product Comparison"
Last order date	Currently, we are receiving many orders and it is taking a considerable amount of time to fulfill them. Therefore, the production discontinuation will be implemented after all orders are fulfilled and inventory is depleted.
Maintenance parts	There are no maintenance parts.
Others	None

Attachment 1

JIS Compatible Earth Leakage Circuit Breaker DV32, DV33, DG32 Series Alternative Product Comparison

Rep.NO.C23007
2023-7-21 Fuji Electric FA Components & Systems Co., Ltd.

Manufacturer name		Fuji Electric FA Components & Systems			Panasonic			Tempearl		
Appearance										
Types		DV32	DV33	DG32	J-0E		J-2E	GT-2EA	GT-31EA	GB-2EA
Dimensions 	a	68	90	68	68	90	68	68	90	68
	b	70	80	70	70	80	70	70	80	70
	c	40	40	40	40	40	40	40	40	40
	d	63	63	63	56	56	56	57	57	57
Element No.		2P0E	3P0E	2P2E	2P0E	3P0E	2P2E	2P0E	3P0E	2P2E
Rated voltage [V]		100-200 shared			100-200 both		100-100/200-200 shared	100-200		100-100/200-200
Rated current [A]		30		15, 20, 30	30		15, 20, 30	30		15, 20, 30
Sensitivity current		15, 30			15, 30			15, 30		15, 30
Breaking capacity [kA]		1.5			2.5		1.5(200V:1)	0.5		100-100/200V:1.5, 200V:1.0